

# SAFETY DATA SHEET

## AB111

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

### SECTION1:Identificationofthesubstance/mixtureand ofthecompany/undertaking

#### 1.1. Product identifier

Product name AB111  
Product number FP-0003963,A03718

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.  
Uses advised against No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

Supplier ABRABOND LTD  
EDWIN AVENUE  
HOO FARM IND EST  
KIDDERMINSTER  
WORCS  
DY11 7RA  
T: +44 (0) 1562 753334  
F: +44 (0) 1562 67595

#### 1.4. Emergency telephone number

Emergency telephone +44 01562 753334 (NOT 24HRS)

### SECTION2:Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

Physical hazards Flam. Liq. 2 - H225  
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336  
STOT RE 2 - H373  
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xn;R48/20. Repr. Cat. 3;R63. Xi;R38. R43. F;R11. N;R51/53. R67.

Physicochemical The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

#### 2.2. Label elements

## AB111

## Pictogram



## Signal word

Danger

## Hazard statements

H315 Causes skin irritation.  
 H225 Highly flammable liquid and vapour.  
 H336 May cause drowsiness or dizziness.  
 H319 Causes serious eye irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H317 May cause an allergic skin reaction.  
 H361d Suspected of damaging the unborn child.  
 H411 Toxic to aquatic life with long lasting effects.

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breathe vapour/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with national regulations.

## Contains

TOLUENE, hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane, ACETONE, ROSIN

## Supplementary precautionary statements

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P314 Get medical advice/attention if you feel unwell.  
 P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.  
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
 P391 Collect spillage.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

2.3. Other hazards

## AB111

This product does not contain any substances classified as PBT or vPvB.

## SECTION3:Composition/informationon ingredients

## 3.2. Mixtures

TOLUENE <span style="float: right;">30-60%</span>		
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0051
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane <span style="float: right;">30-60%</span>		
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 STOT SE 3 - H336 STOT SE 3 - H336 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
ACETONE <span style="float: right;">10-30%</span>		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT SE 3 - H336 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
ROSIN <span style="float: right;">1-5%</span>		
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-0036
Classification Skin Sens. 1 - H317	Classification (67/548/EEC or 1999/45/EC) R43	

## AB111

HEXANE-norm		<1%
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f Asp. Tox. 1 - H304 STOT SE 3 - H336 STOT RE 2 - H373 STOT SE 3 - H336 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67 N;R51/53	
ZINC OXIDE		<1%
CAS number: 1314-13-2	EC number: 215-222-5	
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) N;R50/53	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION4:Firstaid measures

##### 4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
----------------------	---

#### SECTION5:Firefightingmeasures

##### 5.1. Extinguishing media

## AB111

Suitable extinguishing media    Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media    Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards    The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. The product is highly flammable.

Hazardous combustion products    Does not decompose when used and stored as recommended.

### 5.3. Advice for firefighters

Protective actions during firefighting    Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

Special protective equipment for firefighters    Wear chemical protective suit.

## SECTION6:Accidentalrelease measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions    Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Environmental precautions    Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up    Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

Reference to other sections    Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION7:Handlingand storage

### 7.1. Precautions for safe handling

Usage precautions    Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions    Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

Storage class    Flammable liquid storage.

### 7.3. Specific end use(s)

Specific end use(s)    The identified uses for this product are detailed in Section 1.2.

## SECTION8:ExposureControls/personalprotection

## AB111

8.1. Control parametersOccupational exposure limits

## TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m<sup>3</sup>(Sk)

## ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

## HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

ACETONE (CAS: 67-64-1)

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

## Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION9:Physicaland Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Amber.

## AB111

Odour	Characteristic.
Initial boiling point and range	Not determined.
Flash point	-35°C
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6 Upper flammable/explosive limit: 13
Relative density	0.86 @ 20°C
Solubility(ies)	Insoluble in water.
Auto-ignition temperature	200°C
Viscosity	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.

## 9.2. Other information

## SECTION10:Stabilityand reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

## SECTION11:Toxicologicalinformation

11.1. Information on toxicological effects

## Acute toxicity - oral

ATE oral (mg/kg) 6,250.0

## Acute toxicity - dermal

ATE dermal (mg/kg) 6,250.0

Toxicological information on ingredients.TOLUENEAcute toxicity - oral

## AB111

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 2,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 20.0

Species Rat

Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l) 20.0

Species Rat

ATE inhalation (vapours mg/l) 20.0

**SECTION 12: Ecological Information**

12.1. Toxicity

Ecological information on ingredients.

TOLUENE

Acute toxicity - fish , 48 hours, 48 hours: > 1-10 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC<sub>50</sub>, 72 hours: 100 mg/l, Algae

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Ecological information on ingredients.

TOLUENE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Ecological information on ingredients.

TOLUENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

## AB111

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment      This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.TOLUENE

Results of PBT and vPvB assessment      This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects      None known.

Ecological information on ingredients.TOLUENE

Other adverse effects      Not known.

**SECTION13:Disposal considerations**13.1. Waste treatment methods

General information      Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods      Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**SECTION14:Transportinformation**14.1. UN number

UN No. (ADR/RID)      1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID)      ADHESIVES

Proper shipping name (IMDG)      ADHESIVES

Proper shipping name (ICAO)      ADHESIVES

Proper shipping name (ADN)      ADHESIVES

14.3. Transport hazard class(es)14.4. Packing group14.5. Environmental hazards14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

**SECTION15:Regulatoryinformation**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

**SECTION16:Otherinformation**

## AB111

Issued by	Compliance
Revision date	01/06/2015
Revision	20
Risk phrases in full	R11 Highly flammable. R36 Irritating to eyes. R38 Irritating to skin. R43 May cause sensitisation by skin contact. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R62 Possible risk of impaired fertility. R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Store Between	Store Between 5°C - 25°C